

Large-deformation lattice model for dry-woven fabrics including contact

Marco Magliulo
Dr. Ir. Beex Lars
Pr. Zilian Andreas
Stephane Bordas

University of Luxembourg

May 8, 2016



1 The QC method in a nutshell


2 Future Work

Scope of application of QC method

Used to determine the influence of localised microscale phenomena on large-scale responses:

- Atomistic computations, in particular for:
 - ① presence of a defect in a solid (e.g. inclusion) [5]
 - ② Indentation problem
- Crack initiation and propagation [4]
- Simulations of wovens (mesoscale) [2]

Case of a network linear elastic trusses (conservative)



For this simple case, the energy of a lattice node is given by [1]:

$$E_i = \frac{1}{2} \sum_{j \in Bi} E_{ij} = \frac{1}{4} \sum_{j \in Bi} k_{ij} (\Delta L_{ij})^2 \quad (1)$$

with

$$\Delta L_{ij} = \sqrt{(\vec{x}_j - \vec{x}_i)^2} - \sqrt{(\vec{X}_j - \vec{X}_i)^2} \quad (2)$$

knowing that [1] :

$$E_{tot} = \sum_{node} E_i - \mathbf{f}_{ext}^t \mathbf{u} = E_{int} - \mathbf{f}_{ext}^t \mathbf{u} \quad (3)$$

we can determine the min of E_{tot} using the variational principle:

$$\delta E_{tot} = 0 \quad \forall \delta u \quad (4)$$

This problem can be solved using a standard Newton-Raphson algorithm [1]:

$$\delta \mathbf{u}(\mathbf{f}(\mathbf{u}^*) + \mathbf{K}(\mathbf{u}^*)\mathbf{d}(\mathbf{u})) = \mathbf{0} \quad (5)$$


With:

- $\mathbf{f}(\mathbf{u}) = \frac{\partial \mathbf{E}_{\text{tot}}}{\partial \mathbf{u}}$
- \mathbf{K} the stiffness matrix
- \mathbf{u}^* the displacement vector at the previous iteration

Inefficiency comes from:

- 1 The displacement of all the nodes of the lattice has to be found
- 2 Every node has to be taken discretely into account construct the governing equations.

Interpolation of the displacements within the triangles



Use of interpolation functions: $\mathbf{u} = \mathbf{u}_r \Psi$

- The displacement of all the nodes depends only on the displacement of the representative node
- Since $r \ll n$ the solution space is reduced


The equation to solve become [1]:

$$\delta \mathbf{u}_r^T (\boldsymbol{\Psi}^T \mathbf{f}(\mathbf{u}^*) + \boldsymbol{\Psi}^T \mathbf{K}(\mathbf{u}^*) \boldsymbol{\Psi} \mathbf{d}(\mathbf{u}_r)) = \mathbf{0} \quad \forall \delta \mathbf{u}_r \quad (6)$$

But still all the lattice node must be visited to construct \mathbf{f} and \mathbf{K} !

Summation rule

Various summation rule exist.




For the *central summation rule* nodes represent other node within the same interp. triangle through weights ω [1]:

$$f^{c,s}(\mathbf{u}_r) = \sum_{i \in S} \omega_i \Psi^T \mathbf{f}_i \quad (7)$$

$$\mathbf{K}^{c,s}(\mathbf{u}_r) = \sum_{i \in S} \omega_i \Psi^T \mathbf{K}_i \Psi \quad (8)$$

Ill-posed problems

NR not suited for Ill-posed problem (e.g. rigid body motions)
Alternative like the Deepest Descent with Back track Line Search and Armijo Rule for unconstrained optimisation [3]



Future Work

- Implement Trust Region Algorithm
- Inclusion of contacts (inequality constraints)
- Modelling of real materials subjected to large deformations

References I

- [1] LAA Beex, RHJ Peerlings, and MGD Geers.
A quasicontinuum methodology for multiscale analyses of discrete microstructural models.
International Journal for Numerical Methods in Engineering, 87(7):701–718, 2011.
- [2] LAA Beex, RHJ Peerlings, and MGD Geers.
A multiscale quasicontinuum method for lattice models with bond failure and fiber sliding.
Computer Methods in Applied Mechanics and Engineering, 269:108–122, 2014.
- [3] Jorge Nocedal and Stephen J Wright.
Numerical optimization, second edition.
Numerical optimization, pages 497–528, 2006.

References II

- [4] VB Shenoy, R Miller, EB Tadmor, R Phillips, and M Ortiz.
Quasicontinuum models of interfacial structure and deformation.
Physical Review Letters, 80(4):742, 1998.
- [5] Ellad B Tadmor, Michael Ortiz, and Rob Phillips.
Quasicontinuum analysis of defects in solids.
Philosophical Magazine A, 73(6):1529–1563, 1996.

Thanks for your attention