



Algorithmic Decision Theory

Lecture 3: On consensual social ranking

Raymond Bisdorff

FSTC - CSC/ILIAS

4 mars 2020



Content

1. On ranking from different opinions

Definition of the ranking problem

Linear Rankings

Majority margins

2. Types of ranking rules

Borda type rules

Condorcet : Ranking-by-choosing rules

Condorcet : Ranking-by-scoring rules

3. A classification of ranking rules

Condorcet-consistency

M -ordinality and M -invariance

Which ranking rule should we use?

Definition of the ranking problem

A ranking rule is a procedure which aggregates marginal, ie individual voters, experts or criteria based, rankings into a global *consensus ranking* which combines the available preferential information *best* from the marginal viewpoints.




FIGURE – 1. Computing a consensual ranking



Example (A first example : Borda's average ranks)

```
>>> from votingProfiles import *
>>> v = LinearVotingProfile('example1')
>>> v.showLinearBallots()
```

```
  voters      marginal candidate's
(weight)      rankings
v1(8):  ['a', 'c', 'b', 'e', 'd']
v2(7):  ['e', 'b', 'c', 'd', 'a']
v3(4):  ['d', 'c', 'b', 'e', 'a']
v4(4):  ['b', 'd', 'e', 'c', 'a']
v5(2):  ['c', 'd', 'b', 'e', 'a']
```

```
# voters: 25
```

```
>>> v.showRankAnalysisTable()
```

```
----- Borda rank analysis tableau -----
candi- |      candidate x rank      |      Borda
dates  |  1    2    3    4    5    |  score  average
-----|-----|-----
'b'   |  4    7   14    0    0    |   60    2.40
'c'   |  2   12    7    4    0    |   63    2.52
'e'   |  7    0    4   14    0    |   75    3.00
'd'   |  4    6    0    7    8    |   84    3.36
'a'   |  8    0    0    0   17    |   93    3.72
```



Linear Rankings

- A **linear ranking** $R = [a_1, a_2, \dots, a_n]$ is a list of n objects (a set X of candidates or decision alternatives) where the indexes $1 \leq i < j \leq n$ represent a complete preferential ' a_i **better than** a_j ' relation without ties ($a_i > a_j$). The reversed list is called a *linear order*.
- A linear ranking R may be modelled with the help of a *bipolar characteristic function* $r(a_i > a_j) \in \{-1, 0, 1\}$ where :

$$r(a_i > a_j) = \begin{cases} +1 & \text{if } i < j, \\ -1 & \text{if } i > j, \\ 0 & \text{otherwise.} \end{cases}$$

- Notice that reversing a ranking R is achieved by negation : $r(a_i \not> a_j) = -r(a_i > a_j)$ which characterizes the corresponding linear order.

Linear Rankings

- A **linear ranking** $R = [a_1, a_2, \dots, a_n]$ is a list of n objects (a set X of candidates or decision alternatives) where the indexes $1 \leq i < j \leq n$ represent a complete preferential ' a_i **better than** a_j ' relation without ties ($a_i > a_j$). The reversed list is called a *linear order*.
- A linear ranking R may be modelled with the help of a *bipolar characteristic function* $r(a_i > a_j) \in \{-1, 0, 1\}$ where :

$$r(a_i > a_j) = \begin{cases} +1 & \text{if } i < j, \\ -1 & \text{if } i > j, \\ 0 & \text{otherwise.} \end{cases}$$

- Notice that reversing a ranking R is achieved by negation : $r(a_i \not> a_j) = -r(a_i > a_j)$ which characterizes the corresponding linear order.

Linear Rankings

- A **linear ranking** $R = [a_1, a_2, \dots, a_n]$ is a list of n objects (a set X of candidates or decision alternatives) where the indexes $1 \leq i < j \leq n$ represent a complete preferential ' a_i **better than** a_j ' relation without ties ($a_i > a_j$). The reversed list is called a *linear order*.
- A linear ranking R may be modelled with the help of a *bipolar characteristic function* $r(a_i > a_j) \in \{-1, 0, 1\}$ where :

$$r(a_i > a_j) = \begin{cases} +1 & \text{if } i < j, \\ -1 & \text{if } i > j, \\ 0 & \text{otherwise.} \end{cases}$$

- Notice that reversing a ranking R is achieved by negation : $r(a_i \not> a_j) = -r(a_i > a_j)$ which characterizes the corresponding linear order.



Properties of linear rankings

A *linear ranking* $R = [a_1, a_2, \dots, a_n]$ is

- a *transitive* relation, $\forall i, j, k = 1..n$:

$$[(r(a_i > a_j) = +1) \wedge (r(a_j > a_k) = +1)] \Rightarrow (r(a_i > a_k) = +1);$$

- a *complete* relation, $\forall i \neq j$:

$$r((a_i > a_j) \vee (a_j > a_i)) = \max(r(a_i > a_j), r(a_j > a_i)) = +1;$$

- an *irreflexive* relation, $\forall i$:

$$r(a_i > a_i) = 0 \quad /* \text{ We ignore the reflexive relations } */.$$

- A ranking with ties –a collection of ordered equivalence classes– is called a *weak ranking*; its *converse* is called a *preorder*, and its *negation* is called a *weak order*.



Properties of linear rankings

A *linear ranking* $R = [a_1, a_2, \dots, a_n]$ is

- a *transitive* relation, $\forall i, j, k = 1..n$:

$$[(r(a_i > a_j) = +1) \wedge (r(a_j > a_k) = +1)] \Rightarrow (r(a_i > a_k) = +1);$$

- a *complete* relation, $\forall i \neq j$:

$$r((a_i > a_j) \vee (a_j > a_i)) = \max(r(a_i > a_j), r(a_j > a_i)) = +1;$$

- an *irreflexive* relation, $\forall i$:

$$r(a_i > a_i) = 0 \quad /* \text{ We ignore the reflexive relations } */.$$

- A ranking with ties –a collection of ordered equivalence classes– is called a *weak ranking*; its *converse* is called a *preorder*, and its *negation* is called a *weak order*.



Properties of linear rankings

A *linear ranking* $R = [a_1, a_2, \dots, a_n]$ is

- a *transitive* relation, $\forall i, j, k = 1..n$:

$$\left[(r(a_i > a_j) = +1) \wedge (r(a_j > a_k) = +1) \right] \Rightarrow (r(a_i > a_k) = +1);$$

- a *complete* relation, $\forall i \neq j$:

$$r((a_i > a_j) \vee (a_j > a_i)) = \max(r(a_i > a_j), r(a_j > a_i)) = +1;$$

- an *irreflexive* relation, $\forall i$:

$$r(a_i > a_i) = 0 \quad /* \text{ We ignore the reflexive relations } */.$$

- A ranking with ties –a collection of ordered equivalence classes– is called a *weak ranking*; its *converse* is called a *preorder*, and its *negation* is called a *weak order*.



Properties of linear rankings

A *linear ranking* $R = [a_1, a_2, \dots, a_n]$ is

- a *transitive* relation, $\forall i, j, k = 1..n$:

$$\left[(r(a_i > a_j) = +1) \wedge (r(a_j > a_k) = +1) \right] \Rightarrow (r(a_i > a_k) = +1);$$

- a *complete* relation, $\forall i \neq j$:

$$r((a_i > a_j) \vee (a_j > a_i)) = \max(r(a_i > a_j), r(a_j > a_i)) = +1;$$

- an *irreflexive* relation, $\forall i$:

$$r(a_i > a_i) = 0 \quad /* \text{ We ignore the reflexive relations } */.$$

- A ranking with ties – a collection of ordered equivalence classes – is called a *weak ranking*; its *converse* is called a *preorder*, and its *negation* is called a *weak order*.



Majority margins

The **majority margin** $M(x, y)$ counts the *net advantage* of a candidate x over a candidate y . With k voters :

$$\begin{aligned} M(x, y) &= \sum_{k=1}^n (r(x >_k y)) + \sum_{k=1}^n (r(y \not>_k x)) \\ &= \sum_{k=1}^n [r(x >_k y) - r(y >_k x)] \end{aligned}$$

If the profile u consist of **complete** linear rankings, then :

$$M(x, x) = 0 \quad \text{and} \quad M(x, y) + M(y, x) = 0.$$

In this case, indeed :

$$\sum_{k=1}^n (r(x >_k y)) = n - \sum_{k=1}^n (r(y >_k x))$$

Majority margins

The **majority margin** $M(x, y)$ counts the *net advantage* of a candidate x over a candidate y . With k voters :

$$\begin{aligned}
 M(x, y) &= \sum_{k=1}^n (r(x >_k y)) + \sum_{k=1}^n (r(y \not>_k x)) \\
 &= \sum_{k=1}^n [r(x >_k y) - r(y >_k x)]
 \end{aligned}$$

If the profile u consist of **complete** linear rankings, then :

$$M(x, x) = 0 \quad \text{and} \quad M(x, y) + M(y, x) = 0.$$

In this case, indeed :

$$\sum_{k=1}^n (r(x >_k y)) = n - \sum_{k=1}^n (r(y >_k x))$$

Majority margins

The **majority margin** $M(x, y)$ counts the *net advantage* of a candidate x over a candidate y . With k voters :

$$\begin{aligned}
 M(x, y) &= \sum_{k=1}^n (r(x >_k y)) + \sum_{k=1}^n (r(y \not>_k x)) \\
 &= \sum_{k=1}^n [r(x >_k y) - r(y >_k x)]
 \end{aligned}$$

If the profile u consist of **complete** linear rankings, then :

$$M(x, x) = 0 \quad \text{and} \quad M(x, y) + M(y, x) = 0.$$

In this case, indeed :

$$\sum_{k=1}^n (r(x >_k y)) = n - \sum_{k=1}^n (r(y >_k x))$$


Example (Computing majority margins)

```
>>> v
Instance class      : LinearVotingProfile
Instance name      : example1
# Candidates: 5, # Voters: 5
>>> v.showLinearBallots()
  coalition      marginal candidate's
  (weight)              rankings
  v1(8):  ['a', 'c', 'b', 'e', 'd']
  v2(7):  ['e', 'b', 'c', 'd', 'a']
  v3(4):  ['d', 'c', 'b', 'e', 'a']
  v4(4):  ['b', 'd', 'e', 'c', 'a']
  v5(2):  ['c', 'd', 'b', 'e', 'a']
Total number of voters: 25
>>> from votingProfiles import CondorcetDigraph
>>> cd = CondorcetDigraph(v)
>>> cd.showMajorityMargins()
* ---- Relation Table ----
M(x,y) |  'a'  'b'  'c'  'd'  'e'
-----|-----
  'a'  |  0   -9   -9   -9   -9
  'b'  |  9    0   -3   13   11
  'c'  |  9    3    0    9    3
  'd'  |  9  -13   -9    0   -5
  'e'  |  9  -11   -3    5    0
Valuation domain: [-25;+25]
```

The **majority relation** $C(x,y)$ checks if a majority margin $M(x,y)$ is *positive*, ie if there is a majority of rankings which rank candidate x before candidate y :

$$C(x,y) = \begin{cases} +1 & \text{if } M(x,y) > 0 \\ -1 & \text{if } M(x,y) < 0 \\ 0 & \text{otherwise.} \end{cases}$$

```
>>> cdp = PolarisedDigraph(cd,level=0,\
    StrictCut=True,KeepValues=False)
>>> cdp.recodeValuation(-1,1)
>>> cdp.showRelationTable(ndigits=0)
* ---- Relation Table ----
C(x,y) | 'a'  'b'  'c'  'd'  'e'
-----|-----
'a'    |  0   -1   -1   -1   -1
'b'    |  1    0   -1    1    1
'c'    |  1    1    0    1    1
'd'    |  1   -1   -1    0   -1
'e'    |  1   -1   -1    1    0
>>> cdp.exportGraphViz()
```



Rubis Python Server (graphviz), R. Bisdorff, 2008



On ranking from different opinions

1. On ranking from different opinions

Definition of the ranking problem

Linear Rankings

Majority margins

2. Types of ranking rules

Borda type rules

Condorcet : Ranking-by-choosing rules

Condorcet : Ranking-by-scoring rules

3. A classification of ranking rules

Condorcet-consistency

M -ordinality and M -invariance

Which ranking rule should we use?

Ranking rule

- A *profile* $u = \{R_1, R_2, \dots, R_q\}$ is a list of q linear rankings.
- This profile u is the input of a **ranking rule** : $u \rightarrow f(u)$.
- The output of a ranking rule can be :

one (S.R.) or several (M.R.) linear rankings;

- We present hereafter three types of ranking rules :



Ranking rule

- A *profile* $u = \{R_1, R_2, \dots, R_q\}$ is a list of q linear rankings.
- This profile u is the input of a **ranking rule** : $u \rightarrow f(u)$.
- The output of a ranking rule can be :
 - one (*SLR*) or several (*MLR*) *linear* rankings ;
 - one (*SWR*) or several (*MWR*) *weak* rankings (with ties) ;
- We present hereafter three types of ranking rules :

Ranking rule

- A *profile* $u = \{R_1, R_2, \dots, R_q\}$ is a list of q linear rankings.
- This profile u is the input of a **ranking rule** : $u \rightarrow f(u)$.
- The output of a ranking rule can be :
 - one (*SLR*) or several (*MLR*) *linear* rankings ;
 - one (*SWR*) or several (*MWR*) *weak* rankings (with ties).
- We present hereafter three types of ranking rules :

Ranking rule

- A *profile* $u = \{R_1, R_2, \dots, R_q\}$ is a list of q linear rankings.
- This profile u is the input of a **ranking rule** : $u \rightarrow f(u)$.
- The output of a ranking rule can be :
 - one (*SLR*) or several (*MLR*) *linear* rankings ;
 - one (*SWR*) or several (*MWR*) *weak* rankings (with ties).
- We present hereafter three types of ranking rules :

Rank analysis based ranking by scoring rules (first type)

Preference aggregation based ranking rules (second type)

Rank aggregation rules

Ranking rule

- A *profile* $u = \{R_1, R_2, \dots, R_q\}$ is a list of q linear rankings.
- This profile u is the input of a **ranking rule** : $u \rightarrow f(u)$.
- The output of a ranking rule can be :
 - one (*SLR*) or several (*MLR*) *linear* rankings ;
 - one (*SWR*) or several (*MWR*) *weak* rankings (with ties).
- We present hereafter three types of ranking rules :
 1. Rank analysis based ranking-by-scoring rules (Borda type) ;
 2. Pairwise majority margins based rules (Condorcet type)



Ranking rule

- A *profile* $u = \{R_1, R_2, \dots, R_q\}$ is a list of q linear rankings.
- This profile u is the input of a **ranking rule** : $u \rightarrow f(u)$.
- The output of a ranking rule can be :
 - one (*SLR*) or several (*MLR*) *linear* rankings ;
 - one (*SWR*) or several (*MWR*) *weak* rankings (with ties).
- We present hereafter three types of ranking rules :
 1. *Rank analysis* based ranking-by-scoring rules (**Borda** type) ;
 2. *Pairwise majority margins* based rules (**Condorcet** type) :
 - 2.1. Ranking-by-choosing rules ;
 - 2.2. Ranking-by-scoring rules ;



Ranking rule

- A *profile* $u = \{R_1, R_2, \dots, R_q\}$ is a list of q linear rankings.
- This profile u is the input of a **ranking rule** : $u \rightarrow f(u)$.
- The output of a ranking rule can be :
 - one (*SLR*) or several (*MLR*) *linear* rankings ;
 - one (*SWR*) or several (*MWR*) *weak* rankings (with ties).
- We present hereafter three types of ranking rules :
 1. *Rank analysis* based ranking-by-scoring rules (**Borda** type) ;
 2. *Pairwise majority margins* based rules (**Condorcet** type) :
 - 2.1 Ranking-by-choosing rules ;
 - 2.2 Ranking-by-scoring rules.



Ranking rule

- A *profile* $u = \{R_1, R_2, \dots, R_q\}$ is a list of q linear rankings.
- This profile u is the input of a **ranking rule** : $u \rightarrow f(u)$.
- The output of a ranking rule can be :
 - one (*SLR*) or several (*MLR*) *linear* rankings ;
 - one (*SWR*) or several (*MWR*) *weak* rankings (with ties).
- We present hereafter three types of ranking rules :
 1. *Rank analysis* based ranking-by-scoring rules (**Borda** type) ;
 2. *Pairwise majority margins* based rules (**Condorcet** type) :
 - 2.1 Ranking-by-choosing rules ;
 - 2.2 Ranking-by-scoring rules.



Ranking rule

- A *profile* $u = \{R_1, R_2, \dots, R_q\}$ is a list of q linear rankings.
- This profile u is the input of a **ranking rule** : $u \rightarrow f(u)$.
- The output of a ranking rule can be :
 - one (*SLR*) or several (*MLR*) *linear* rankings ;
 - one (*SWR*) or several (*MWR*) *weak* rankings (with ties).
- We present hereafter three types of ranking rules :
 1. *Rank analysis* based ranking-by-scoring rules (**Borda** type) ;
 2. *Pairwise majority margins* based rules (**Condorcet** type) :
 - 2.1 Ranking-by-choosing rules ;
 - 2.2 Ranking-by-scoring rules.

Ranking rule

- A *profile* $u = \{R_1, R_2, \dots, R_q\}$ is a list of q linear rankings.
- This profile u is the input of a **ranking rule** : $u \rightarrow f(u)$.
- The output of a ranking rule can be :
 - one (*SLR*) or several (*MLR*) *linear* rankings ;
 - one (*SWR*) or several (*MWR*) *weak* rankings (with ties).
- We present hereafter three types of ranking rules :
 1. *Rank analysis* based ranking-by-scoring rules (**Borda** type) ;
 2. *Pairwise majority margins* based rules (**Condorcet** type) :
 - 2.1 Ranking-by-choosing rules ;
 - 2.2 Ranking-by-scoring rules.

Borda's candidate-to-rank matrix

The *candidate-to-rank matrix* Q_{ij} counts the number of times the candidate a_i is ranked at position j .

$$Q_{ij} = \{ \# \text{ rankings : } a_i \text{ is ranked at the } j \text{ th position} \}$$

Borda rank analysis tableau

voter's weight	marginal ranking	candi- dates	Q _{ij}				
			1	2	3	4	5
8	acbed	'a'	8	0	0	0	17
7	ebcda	'b'	4	7	14	0	0
4	dcbea	'c'	2	12	7	4	0
4	bdeca	'd'	4	6	0	7	8
2	cdbea	'e'	7	0	4	14	0



Borda's rule

- A **Borda score** B is computed for each candidate a_i as follows :

$$B(a_i) = \sum_{j=1}^n (Q_{ij} \times j)$$

The candidates are ranked from the lowest to the largest according to the Borda scores (to be mimized).

- A generalization of the Borda rule is to use any set of weights representing the ranks. Let $w_1 < w_2 < \dots < w_n$ be increasing weights of the ranks. Then the Borda scores B are defined as follows :

$$B(a_i) = \sum_{j=1}^n (Q_{ij} \times w_j)$$

- The **Borda ranking** \succeq_B is the weak ranking defined as follows :

$$\forall x, y \in X, (x, y) \in \succeq_B \Leftrightarrow b_x \leq b_y.$$

Borda's rule

- A **Borda score** B is computed for each candidate a_i as follows :

$$B(a_i) = \sum_{j=1}^n (Q_{ij} \times j)$$

The candidates are ranked from the lowest to the largest according to the Borda scores (to be mimized).

- A generalization of the Borda rule is to use any set of weights representing the ranks. Let $w_1 < w_2 < \dots < w_n$ be increasing weights of the ranks. Then the Borda scores B are defined as follows :

$$B(a_i) = \sum_{j=1}^n (Q_{ij} \times w_j)$$

- The **Borda ranking** \succeq_B is the weak ranking defined as follows :

$$\forall x, y \in X, (x, y) \in \succeq_B \Leftrightarrow b_x \leq b_y.$$

Borda's rule

- A **Borda score** B is computed for each candidate a_i as follows :

$$B(a_i) = \sum_{j=1}^n (Q_{ij} \times j)$$

The candidates are ranked from the lowest to the largest according to the Borda scores (to be mimized).

- A generalization of the Borda rule is to use any set of weights representing the ranks. Let $w_1 < w_2 < \dots < w_n$ be increasing weights of the ranks. Then the Borda scores B are defined as follows :

$$B(a_i) = \sum_{j=1}^n (Q_{ij} \times w_j)$$

- The **Borda ranking** \succeq_B is the weak ranking defined as follows :

$$\forall x, y \in X, (x, y) \in \succeq_B \Leftrightarrow b_x \leq b_y.$$

Borda's rule

- A **Borda score** B is computed for each candidate a_i as follows :

$$B(a_i) = \sum_{j=1}^n (Q_{ij} \times j)$$

The candidates are ranked from the lowest to the largest according to the Borda scores (to be mimized).

- A generalization of the Borda rule is to use any set of weights representing the ranks. Let $w_1 < w_2 < \dots < w_n$ be increasing weights of the ranks. Then the Borda scores B are defined as follows :

$$B(a_i) = \sum_{j=1}^n (Q_{ij} \times w_j)$$

- The **Borda ranking** \succeq_B is the weak ranking defined as follows :

$$\forall x, y \in X, \quad (x, y) \in \succeq_B \Leftrightarrow b_x \leq b_y.$$

Example (Borda's weighted scores)

Borda rank analysis tableau								
candi- dates	candidate x rank					Borda scores		
	1	2	3	4	5	w1	w2	
'b'	4	7	14	0	0	60	88	
'c'	2	12	7	4	0	63	85	
'e'	7	0	4	14	0	75	111	
'd'	4	6	0	7	8	84	122	
'a'	8	0	0	0	17	93	144	
w1	1	2	3	4	5			
w2	1	2	5	6	8			

We observe two different rankings : R_{w1} : *bceda* and R_{w2} : *cbeda*, depending hence on the actual rank weights. Notice that the original Borda ranking R_{w1} is not consistent with the majority relation, which is R_{w2} . Given the ordinal nature of the input data, there is no information on how to assign weights to the ranks.

Generalized ranks-based rules

Definition (**Borda type Rules**, *SWR*/candidate×rank analysis)

Let r_{ik} , $i = 1..n$, $k = 1..q$ be the rank of candidate a_i in ranking R_k , and w_1, w_2, \dots, w_q be a set of given rank weights. We may rank :

1. according to the average weighted rank :

$$B(a_i) = \frac{1}{q} \sum_{k=1}^q (r_{ik} \times w_k)$$

2. according to the weighted median rank :

$$B(a_i) = \text{median} [(r_{i1} \times w_1), (r_{i2} \times w_2), \dots, (r_{iq} \times w_q)]$$

3. by minimizing a given distance function (Cook & Seiford).

Generalized ranks-based rules

Definition (**Borda type Rules**, *SWR*/candidate×rank analysis)

Let r_{ik} , $i = 1..n$, $k = 1..q$ be the rank of candidate a_i in ranking R_k , and w_1, w_2, \dots, w_q be a set of given rank weights. We may rank :

1. according to the average weighted rank :

$$B(a_i) = \frac{1}{q} \sum_{k=1}^q (r_{ik} \times w_k)$$

2. according to the weighted median rank :

$$B(a_i) = \text{median} [(r_{i1} \times w_1), (r_{i2} \times w_2), \dots, (r_{iq} \times w_q)]$$

3. by minimizing a given distance function (Cook & Seiford).

Generalized ranks-based rules

Definition (Borda type Rules, *SWR*/candidate × rank analysis)

Let r_{ik} , $i = 1..n$, $k = 1..q$ be the rank of candidate a_i in ranking R_k , and w_1, w_2, \dots, w_q be a set of given rank weights. We may rank :

1. according to the average weighted rank :

$$B(a_i) = \frac{1}{q} \sum_{k=1}^q (r_{ik} \times w_k)$$

2. according to the weighted median rank :

$$B(a_i) = \text{median} [(r_{i1} \times w_1), (r_{i2} \times w_2), \dots, (r_{iq} \times w_q)]$$

3. by minimizing a given distance function (Cook & Seiford).

Generalized ranks-based rules

Definition (Borda type Rules, *SWR*/candidate×rank analysis)

Let r_{ik} , $i = 1..n$, $k = 1..q$ be the rank of candidate a_i in ranking R_k , and w_1, w_2, \dots, w_q be a set of given rank weights. We may rank :

1. according to the average weighted rank :

$$B(a_i) = \frac{1}{q} \sum_{k=1}^q (r_{ik} \times w_k)$$

2. according to the weighted median rank :

$$B(a_i) = \text{median} [(r_{i1} \times w_1), (r_{i2} \times w_2), \dots, (r_{iq} \times w_q)]$$

3. by minimizing a given distance function (Cook & Seiford).



Condorcet : Ranking-by-choosing Rules

Definition (**Kohler's Rule**, *MLR*/majority margins $M(x, y)$)

Optimistic sequential **maximin rule**. At step r (where r goes from 1 to n) :

1. Compute for each candidate x the smallest $M(x, y)$ ($x \neq y$) ;
2. Select the candidate for which this minimum is maximal. If there are ties select in lexicographic order ;
3. Put the selected candidate at rank r in the final ranking ;
4. Delete the row and the column corresponding to the selected candidate and restart from (1).

Condorcet : Ranking-by-choosing Rules

Definition (**Kohler's Rule**, *MLR*/majority margins $M(x, y)$)

Optimistic sequential **maximin rule**. At step r (where r goes from 1 to n) :

1. Compute for each candidate x the smallest $M(x, y)$ ($x \neq y$) ;
2. Select the candidate for which this minimum is maximal. If there are ties select in lexicographic order ;
3. Put the selected candidate at rank r in the final ranking ;
4. Delete the row and the column corresponding to the selected candidate and restart from (1).



Condorcet : Ranking-by-choosing Rules

Definition (**Kohler's Rule**, *MLR*/majority margins $M(x, y)$)

Optimistic sequential **maximin rule**. At step r (where r goes from 1 to n) :

1. Compute for each candidate x the smallest $M(x, y)$ ($x \neq y$) ;
2. Select the candidate for which this minimum is maximal. If there are ties select in lexicographic order ;
3. Put the selected candidate at rank r in the final ranking ;
4. Delete the row and the column corresponding to the selected candidate and restart from (1).



Condorcet : Ranking-by-choosing Rules

Definition (**Kohler's Rule**, *MLR*/majority margins $M(x, y)$)

Optimistic sequential **maximin rule**. At step r (where r goes from 1 to n) :

1. Compute for each candidate x the smallest $M(x, y)$ ($x \neq y$) ;
2. Select the candidate for which this minimum is maximal. If there are ties select in lexicographic order ;
3. Put the selected candidate at rank r in the final ranking ;
4. Delete the row and the column corresponding to the selected candidate and restart from (1).

Condorcet : Ranking-by-choosing Rules

Definition (**Kohler's Rule**, *MLR*/majority margins $M(x, y)$)

Optimistic sequential **maximin rule**. At step r (where r goes from 1 to n) :

1. Compute for each candidate x the smallest $M(x, y)$ ($x \neq y$) ;
2. Select the candidate for which this minimum is maximal. If there are ties select in lexicographic order ;
3. Put the selected candidate at rank r in the final ranking ;
4. Delete the row and the column corresponding to the selected candidate and restart from (1).

Example (Kohler's ranking rule)

4	abcd
4	dcab
4	cabd
5	dbca
1	cbda
3	bcad
4	dabc
2	cdab
2	bacd
1	acdb

	a	b	c	d	min
a		8	-8	-2	-8
b	-8		6	-2	-8
c	8	-6		4	-6
d	2	2	-4		-4

	a	b	c	min
a		8	-8	-8
b	-8		6	-8
c	8	-6		-6

	a	b	min
a		8	8
b	-8		-8

Kohler's ranking : $d > c > a > b$

FIGURE – 2. Source : Cl. Lamboray



Ranking-by-choosing Rules – continue

Definition (**Arrow & Raynaud's Rule**, *MLR*/majority margins $M(x, y)$)

Pessimistic (prudent) sequential **minmax rule**. At step r (where r goes from 1 to n) :

1. Compute for each candidate x the largest $M(x, y)$ ($x \neq y$) ;
2. Select the candidate for which this maximum is minimal. If there are ties select the candidates in lexicographic order ;
3. Put the selected candidate at rank $n - r + 1$ in the final ranking ;
4. Delete the row and the column corresponding to the selected candidate and restart from (1).

Ranking-by-choosing Rules – continue

Definition (**Arrow & Raynaud's Rule**, *MLR*/majority margins $M(x, y)$)

Pessimistic (prudent) sequential **minmax rule**. At step r (where r goes from 1 to n) :

1. Compute for each candidate x the largest $M(x, y)$ ($x \neq y$) ;
2. Select the candidate for which this maximum is minimal. If there are ties select the candidates in lexicographic order ;
3. Put the selected candidate at rank $n - r + 1$ in the final ranking ;
4. Delete the row and the column corresponding to the selected candidate and restart from (1).

Ranking-by-choosing Rules – continue

Definition (**Arrow & Raynaud's Rule**, *MLR*/majority margins $M(x, y)$)

Pessimistic (prudent) sequential **minmax rule**. At step r (where r goes from 1 to n) :

1. Compute for each candidate x the largest $M(x, y)$ ($x \neq y$) ;
2. Select the candidate for which this maximum is minimal. If there are ties select the candidates in lexicographic order ;
3. Put the selected candidate at rank $n - r + 1$ in the final ranking ;
4. Delete the row and the column corresponding to the selected candidate and restart from (1).



Ranking-by-choosing Rules – continue

Definition (**Arrow & Raynaud's Rule**, *MLR*/majority margins $M(x, y)$)

Pessimistic (prudent) sequential **minmax rule**. At step r (where r goes from 1 to n) :

1. Compute for each candidate x the largest $M(x, y)$ ($x \neq y$) ;
2. Select the candidate for which this maximum is minimal. If there are ties select the candidates in lexicographic order ;
3. Put the selected candidate at rank $n - r + 1$ in the final ranking ;
4. Delete the row and the column corresponding to the selected candidate and restart from (1).

Ranking-by-choosing Rules – continue

Definition (**Arrow & Raynaud's Rule**, *MLR*/majority margins $M(x, y)$)

Pessimistic (prudent) sequential **minmax rule**. At step r (where r goes from 1 to n) :

1. Compute for each candidate x the largest $M(x, y)$ ($x \neq y$) ;
2. Select the candidate for which this maximum is minimal. If there are ties select the candidates in lexicographic order ;
3. Put the selected candidate at rank $n - r + 1$ in the final ranking ;
4. Delete the row and the column corresponding to the selected candidate and restart from (1).

Ranking-by-choosing Rules – continue

Definition (**Ranked Pairs' Rule**, *MLR*/majority margins $M(x, y)$)

1. Rank in decreasing order the ordered pairs (x, y) of candidates according to their majority margin $M(x, y)$.
2. Take any linear ranking compatible with this weak order.
3. Consider the pairs (x, y) in that order and do the following :

if x is ranked

higher than y

Ranking-by-choosing Rules – continue

Definition (**Ranked Pairs' Rule**, *MLR*/majority margins $M(x, y)$)

1. Rank in decreasing order the ordered pairs (x, y) of candidates according to their majority margin $M(x, y)$.
2. Take any linear ranking compatible with this weak order.
3. Consider the pairs (x, y) in that order and do the following :
 1. If the considered pair creates a cycle with the already blocked pairs, skip this pair.
 2. If the considered pair does not create a cycle with the already blocked pairs, block this pair.

Ranking-by-choosing Rules – continue

Definition (**Ranked Pairs' Rule**, *MLR*/majority margins $M(x, y)$)

1. Rank in decreasing order the ordered pairs (x, y) of candidates according to their majority margin $M(x, y)$.
2. Take any linear ranking compatible with this weak order.
3. Consider the pairs (x, y) in that order and do the following :
 - 3.1 If the considered pair creates a cycle with the already blocked pairs, skip this pair;
 - 3.2 If the considered pair does not create a cycle with the already blocked pairs, block this pair.



Ranking-by-choosing Rules – continue

Definition (**Ranked Pairs' Rule**, *MLR*/majority margins $M(x, y)$)

1. Rank in decreasing order the ordered pairs (x, y) of candidates according to their majority margin $M(x, y)$.
2. Take any linear ranking compatible with this weak order.
3. Consider the pairs (x, y) in that order and do the following :
 - 3.1 If the considered pair creates a cycle with the already blocked pairs, skip this pair ;
 - 3.2 If the considered pair does not create a cycle with the already blocked pairs, block this pair.

Ranking-by-choosing Rules – continue

Definition (**Ranked Pairs' Rule**, *MLR*/majority margins $M(x, y)$)

1. Rank in decreasing order the ordered pairs (x, y) of candidates according to their majority margin $M(x, y)$.
2. Take any linear ranking compatible with this weak order.
3. Consider the pairs (x, y) in that order and do the following :
 - 3.1 If the considered pair creates a cycle with the already blocked pairs, skip this pair ;
 - 3.2 If the considered pair does not create a cycle with the already blocked pairs, block this pair.

Ranking-by-choosing Rules – continue

Definition (**Ranked Pairs' Rule**, *MLR*/majority margins $M(x, y)$)


1. Rank in decreasing order the ordered pairs (x, y) of candidates according to their majority margin $M(x, y)$.
2. Take any linear ranking compatible with this weak order.
3. Consider the pairs (x, y) in that order and do the following :
 - 3.1 If the considered pair creates a cycle with the already blocked pairs, skip this pair ;
 - 3.2 If the considered pair does not create a cycle with the already blocked pairs, block this pair.

Example (Ranked Pairs rule)

	a	b	c	d
a		8	-8	-2
b	-8		6	-2
c	8	-6		4
d	2	2	-4	


(c,a) (a,b)	8
(b,c)	6
(c,d)	4
(d,a) (d,b)	2
(a,d) (b,d)	-2
(d,c)	-4
(c,b)	-6
(a,c) (b,a)	-8

c
↓
a
↓
b



c
↓
a
↓
b

c ↘
d



Ranked Pairs ranking : $c > d > a > b$

FIGURE – 3. Source : Cl. Lamboray

Example (Condorcet : Ranking-by-choosing)

```
>>> from linearOrders import *
>>> ko = KohlerOrder(cd)
>>> ko.kohlerRanking
['c', 'b', 'e', 'd', 'a']
>>> cdcd = ~(-cd) # codual of cd
>>> ar = KohlerOrder(cdcd) # Arrow-Raynaud rule
>>> ar.kohlerRanking
['c', 'b', 'e', 'd', 'a']
>>> rp = RankedPairsOrder(cd)
>>> rp.rankedPairsRanking
['c', 'b', 'e', 'd', 'a']
```

Kohler's, Arrow&Raynaud's and the RankedPairs rule all result in the same unique linear ranking : *'cbeda'*, which corresponds to the majority relation *C*.

Condorcet : Ranking-by-scoring rules

Definition (**NetFlows Rule**, *MWR*/majority margins $M(x, y)$)

- The idea is that the more a given candidate beats other candidates the better it is.
- Similarly, the more other candidates beat a given candidate, the lower this candidate should be ranked.
- The **NetFlows score** n_x of candidate x is defined as follows :

$$n_x = \sum_y [M(x, y) - M(y, x)].^1$$

- The **NetFlows ranking** \succeq_N is the weak ranking defined as follows : $\forall x, y \in X, (x, y) \in \succeq_N \Leftrightarrow n_x \geq n_y$.

1. Notice that in the case of linear profiles, we may drop the $-M(y, x)$ term due to the zero sum property.

Condorcet : Ranking-by-scoring rules

Definition (**NetFlows Rule**, *MWR*/majority margins $M(x, y)$)

- The idea is that the more a given candidate beats other candidates the better it is.
- Similarly, the more other candidates beat a given candidate, the lower this candidate should be ranked.
- The **NetFlows score** n_x of candidate x is defined as follows :

$$n_x = \sum_y [M(x, y) - M(y, x)].^1$$

- The **NetFlows ranking** \succeq_N is the weak ranking defined as follows : $\forall x, y \in X, (x, y) \in \succeq_N \Leftrightarrow n_x \geq n_y$.

1. Notice that in the case of linear profiles, we may drop the $-M(y, x)$ term due to the zero sum property.

Condorcet : Ranking-by-scoring rules

Definition (**NetFlows Rule**, *MWR*/majority margins $M(x, y)$)

- The idea is that the more a given candidate beats other candidates the better it is.
- Similarly, the more other candidates beat a given candidate, the lower this candidate should be ranked.
- The **NetFlows score** n_x of candidate x is defined as follows :

$$n_x = \sum_y [M(x, y) - M(y, x)].^1$$

- The **NetFlows ranking** \succeq_N is the weak ranking defined as follows : $\forall x, y \in X, (x, y) \in \succeq_N \Leftrightarrow n_x \geq n_y$.

1. Notice that in the case of linear profiles, we may drop the $-M(y, x)$ term due to the zero sum property.

Condorcet : Ranking-by-scoring rules

Definition (**NetFlows Rule**, *MWR*/majority margins $M(x, y)$)

- The idea is that the more a given candidate beats other candidates the better it is.
- Similarly, the more other candidates beat a given candidate, the lower this candidate should be ranked.
- The **NetFlows score** n_x of candidate x is defined as follows :

$$n_x = \sum_y [M(x, y) - M(y, x)].^1$$

- The **NetFlows ranking** \succeq_N is the weak ranking defined as follows : $\forall x, y \in X, (x, y) \in \succeq_N \Leftrightarrow n_x \geq n_y$.

1. Notice that in the case of linear profiles, we may drop the $-M(y, x)$ term due to the zero sum property.

Condorcet : Ranking-by-scoring rules

Definition (**NetFlows Rule**, *MWR*/majority margins $M(x, y)$)

- The idea is that the more a given candidate beats other candidates the better it is.
- Similarly, the more other candidates beat a given candidate, the lower this candidate should be ranked.
- The **NetFlows score** n_x of candidate x is defined as follows :

$$n_x = \sum_y [M(x, y) - M(y, x)].^1$$

- The **NetFlows ranking** \succeq_N is the weak ranking defined as follows : $\forall x, y \in X, (x, y) \in \succeq_N \Leftrightarrow n_x \geq n_y$.

1. Notice that in the case of linear profiles, we may drop the $-M(y, x)$ term due to the zero sum property.

Condorcet : Ranking-by-scoring rules

Definition (**Copeland's Rule**, *MWR*/majority relation $C(x, y)$)

- The idea is that the more a given candidate beats other candidates at majority the better it should be ranked.
- Similarly, the more other candidates beat a given candidate at majority, the lower this candidate should be ranked.
- The **Copeland score** c_x of candidate x is defined as follows :

$$\begin{aligned} c_x &= \#\{y \neq x \in X : M(x, y) > 0\} \\ &\quad - \#\{y \neq x \in X : M(y, x) > 0\} \\ &= \sum_y (C(x, y) - C(y, x)). \end{aligned}$$

- The Copeland ranking \succeq_C is the weak ranking defined as follows : $\forall x, y \in X, (x, y) \in \succeq_C \Leftrightarrow c_x \geq c_y$.

Condorcet : Ranking-by-scoring rules

Definition (**Copeland's Rule**, *MWR*/majority relation $C(x, y)$)

- The idea is that the more a given candidate beats other candidates at majority the better it should be ranked.
- Similarly, the more other candidates beat a given candidate at majority, the lower this candidate should be ranked.
- The **Copeland score** c_x of candidate x is defined as follows :

$$\begin{aligned} c_x &= \#\{y \neq x \in X : M(x, y) > 0\} \\ &\quad - \#\{y \neq x \in X : M(y, x) > 0\} \\ &= \sum_y (C(x, y) - C(y, x)). \end{aligned}$$

- The **Copeland ranking** \succeq_C is the weak ranking defined as follows : $\forall x, y \in X, (x, y) \in \succeq_C \Leftrightarrow c_x \geq c_y$.

Condorcet : Ranking-by-scoring rules

Definition (**Copeland's Rule**, *MWR*/majority relation $C(x, y)$)

- The idea is that the more a given candidate beats other candidates at majority the better it should be ranked.
- Similarly, the more other candidates beat a given candidate at majority, the lower this candidate should be ranked.
- The **Copeland score** c_x of candidate x is defined as follows :

$$\begin{aligned} c_x &= \#\{y \neq x \in X : M(x, y) > 0\} \\ &\quad - \#\{y \neq x \in X : M(y, x) > 0\} \\ &= \sum_y (C(x, y) - C(y, x)). \end{aligned}$$

- The **Copeland ranking** \succeq_C is the weak ranking defined as follows : $\forall x, y \in X, (x, y) \in \succeq_C \Leftrightarrow c_x \geq c_y$.

Condorcet : Ranking-by-scoring rules

Definition (**Copeland's Rule**, *MWR*/majority relation $C(x, y)$)

- The idea is that the more a given candidate beats other candidates at majority the better it should be ranked.
- Similarly, the more other candidates beat a given candidate at majority, the lower this candidate should be ranked.
- The **Copeland score** c_x of candidate x is defined as follows :

$$\begin{aligned} c_x &= \#\{y \neq x \in X : M(x, y) > 0\} \\ &\quad - \#\{y \neq x \in X : M(y, x) > 0\} \\ &= \sum_y (C(x, y) - C(y, x)). \end{aligned}$$

- The **Copeland ranking** \succeq_C is the weak ranking defined as follows : $\forall x, y \in X, (x, y) \in \succeq_C \Leftrightarrow c_x \geq c_y$.

Condorcet : Ranking-by-scoring rules

Definition (**Copeland's Rule**, *MWR*/majority relation $C(x, y)$)

- The idea is that the more a given candidate beats other candidates at majority the better it should be ranked.
- Similarly, the more other candidates beat a given candidate at majority, the lower this candidate should be ranked.
- The **Copeland score** c_x of candidate x is defined as follows :

$$\begin{aligned} c_x &= \#\{y \neq x \in X : M(x, y) > 0\} \\ &\quad - \#\{y \neq x \in X : M(y, x) > 0\} \\ &= \sum_y (C(x, y) - C(y, x)). \end{aligned}$$

- The **Copeland ranking** \succeq_C is the weak ranking defined as follows : $\forall x, y \in X, (x, y) \in \succeq_C \Leftrightarrow c_x \geq c_y$.

Condorcet : Ranking-by-scoring rules

Definition (Kemeny's Rule, MLR/majority margins $M(x, y)$)

- The idea is finding a compromise ranking R that minimizes the distance to the q marginal linear rankings of the voting profile according to the symmetric difference measure : δ . If R_1 and R_2 are two relations, $\delta(R_1, R_2) = |R_1 \oplus R_2| / 2$.
- The **Kemeny ranking**, also called *median* ranking, R^* is a solution of the following optimization problem :

$$\min_{\arg R} \delta(M, R) \quad \equiv \quad \max_{\arg R} \sum_{(x,y) \in R} [M(x, y) \times r(x R y)]$$

such that R is a linear ranking.

- The distance $\delta(M, R^*)$ is called the **Kemeny index** of a preference profile. Computing the Kemeny index is an NP-complete problem and Kemeny rankings are generally not unique.



Condorcet : Ranking-by-scoring rules

Definition (**Kemeny's Rule**, *MLR*/majority margins $M(x, y)$)

- The idea is finding a compromise ranking R that minimizes the distance to the q marginal linear rankings of the voting profile according to the symmetric difference measure : δ . If R_1 and R_2 are two relations, $\delta(R_1, R_2) = |R_1 \oplus R_2| / 2$.
- The **Kemeny ranking**, also called *median* ranking, R^* is a solution of the following optimization problem :

$$\min_{\arg R} \delta(M, R) \quad \equiv \quad \max_{\arg R} \sum_{(x,y) \in R} [M(x, y) \times r(x R y)]$$

such that R is a linear ranking.

- The distance $\delta(M, R^*)$ is called the **Kemeny index** of a preference profile. Computing the Kemeny index is an NP-complete problem and Kemeny rankings are generally not unique.



Condorcet : Ranking-by-scoring rules

Definition (**Kemeny's Rule**, *MLR*/majority margins $M(x, y)$)

- The idea is finding a compromise ranking R that minimizes the distance to the q marginal linear rankings of the voting profile according to the symmetric difference measure : δ . If R_1 and R_2 are two relations, $\delta(R_1, R_2) = |R_1 \oplus R_2| / 2$.
- The **Kemeny ranking**, also called *median* ranking, R^* is a solution of the following optimization problem :

$$\min_{\arg R} \delta(M, R) \quad \equiv \quad \max_{\arg R} \sum_{(x,y) \in R} [M(x, y) \times r(x R y)]$$

such that R is a linear ranking.

- The distance $\delta(M, R^*)$ is called the **Kemeny index** of a preference profile. Computing the Kemeny index is an NP-complete problem and Kemeny rankings are generally not unique.



Condorcet : Ranking-by-scoring rules

Definition (Kemeny's Rule, MLR/majority margins $M(x, y)$)

- The idea is finding a compromise ranking R that minimizes the distance to the q marginal linear rankings of the voting profile according to the symmetric difference measure : δ . If R_1 and R_2 are two relations, $\delta(R_1, R_2) = |R_1 \oplus R_2| / 2$.
- The **Kemeny ranking**, also called *median* ranking, R^* is a solution of the following optimization problem :

$$\min_{\arg R} \delta(M, R) \quad \equiv \quad \max_{\arg R} \sum_{(x,y) \in R} [M(x, y) \times r(x R y)]$$

such that R is a linear ranking.

- The distance $\delta(M, R^*)$ is called the **Kemeny index** of a preference profile. Computing the Kemeny index is an NP-complete problem and Kemeny rankings are generally not unique.



Condorcet : Ranking-by-scoring rules

Definition (**Slater's Rule**, *MLR*/majority relation $C(x, y)$)

- The idea is to select a ranking that is closest according to the symmetric difference distance δ to the Condorcet digraph's polarized relation $M_{>0}$.
- The **Slater** ranking R^* is a solution of the following optimization problem :

$$\operatorname{minarg}_R \delta(M_{>0}, R) \quad \equiv \quad \operatorname{maxarg}_R \sum_{(x,y) \in R} [C(x,y) \times r(xRy)]$$

such that R is a linear ranking.

- The distance $\delta(R^*, M_{>0})$ is called the **Slater index** of a preference profile. Computing the Slater index of a profile is an NP-hard problem and Slater rankings are even less unique than Kemeny rankings.



Condorcet : Ranking-by-scoring rules

Definition (**Slater's Rule**, *MLR*/majority relation $C(x, y)$)

- The idea is to select a ranking that is closest according to the symmetric difference distance δ to the Condorcet digraph's polarized relation $M_{>0}$.
- The **Slater** ranking R^* is a solution of the following optimization problem :

$$\operatorname{minarg}_R \delta(M_{>0}, R) \quad \equiv \quad \operatorname{maxarg}_R \sum_{(x,y) \in R} [C(x,y) \times r(xRy)]$$

such that R is a linear ranking.

- The distance $\delta(R^*, M_{>0})$ is called the **Slater index** of a preference profile. Computing the Slater index of a profile is an NP-hard problem and Slater rankings are even less unique than Kemeny rankings.

Condorcet : Ranking-by-scoring rules

Definition (**Slater's Rule**, *MLR*/majority relation $C(x, y)$)

- The idea is to select a ranking that is closest according to the symmetric difference distance δ to the Condorcet digraph's polarized relation $M_{>0}$.
- The **Slater** ranking R^* is a solution of the following optimization problem :

$$\operatorname{minarg}_R \delta(M_{>0}, R) \quad \equiv \quad \operatorname{maxarg}_R \sum_{(x,y) \in R} [C(x, y) \times r(x R y)]$$

such that R is a linear ranking.

- The distance $\delta(R^*, M_{>0})$ is called the **Slater index** of a preference profile. Computing the Slater index of a profile is an NP-hard problem and Slater rankings are even less unique than Kemeny rankings.



Condorcet : Ranking-by-scoring rules

Definition (**Slater's Rule**, *MLR*/majority relation $C(x, y)$)

- The idea is to select a ranking that is closest according to the symmetric difference distance δ to the Condorcet digraph's polarized relation $M_{>0}$.
- The **Slater** ranking R^* is a solution of the following optimization problem :

$$\operatorname{minarg}_R \delta(M_{>0}, R) \quad \equiv \quad \operatorname{maxarg}_R \sum_{(x,y) \in R} [C(x, y) \times r(x R y)]$$

such that R is a linear ranking.

- The distance $\delta(R^*, M_{>0})$ is called the **Slater index** of a preference profile. Computing the Slater index of a profile is an NP-hard problem and Slater rankings are even less unique than Kemeny rankings.

Example (Condorcet : ranking-by-scoring)

```
* ---- Majority margins -----
Mxy  |   'a'   'b'   'c'   'd'   'e'
'a'  |    0   -9   -9   -9   -9
'b'  |    9    0   -3   13   11
'c'  |    9    3    0    9    3
'd'  |    9  -13   -9    0   -5
'e'  |    9  -11   -3    5    0

>>> cd.computeNetFlowsRanking(Debug=True)
OrderedDict([('b',60),('c',48),('e',0),('d',-36),('a',-72.0)])
['b', 'c', 'e', 'd', 'a']

>>> cd.computeCopelandRanking(Debug=True)
OrderedDict([('c', 4), ('b', 2), ('e', 0), ('d', -2), ('a', -4)])
['c', 'b', 'e', 'd', 'a']

>>> from linearOrders import KemenyOrder
>>> ke = KemenyOrder(cd); ke.maximalRankings
[['c', 'b', 'e', 'd', 'a']]

>>> kecd = KemenyOrder(cdc); kecd.maximalRankings
[['c', 'b', 'e', 'd', 'a']]
```

The NetFlows rule, like the Borda rule, inverts the two top ranked candidates : *'bceda'*, whereas Copeland's, Kemeny's and Slater's rules result again in the same unique ranking : *'cbeda'*.



Content Lecture 3

1. On ranking from different opinions

Definition of the ranking problem

Linear Rankings

Majority margins

2. Types of ranking rules

Borda type rules

Condorcet : Ranking-by-choosing rules

Condorcet : Ranking-by-scoring rules

3. A classification of ranking rules

Condorcet-consistency

M -ordinality and M -invariance

Which ranking rule should we use?



A classification of ranking rules

Definition (Condorcet-consistency)

A ranking rule is **Condorcet-consistent** if the following holds :
*If the majority relation is a linear ranking, then this ranking is the **unique** solution of the ranking rule.*

Property (Condorcet consistent rules)

Kemeny's, Slater's, Copeland's, Kohler's and the RankedPairs rule are all Condorcet-consistent. The Borda and the NetFlows rules are, both, not Condorcet-consistent.



A classification of ranking rules

Definition (Condorcet-consistency)

A ranking rule is **Condorcet-consistent** if the following holds :
*If the majority relation is a linear ranking, then this ranking is the **unique** solution of the ranking rule.*

Property (Condorcet consistent rules)

Kemeny's, Slater's, Copeland's, Kohler's and the RankedPairs rule are all Condorcet-consistent. The Borda and the NetFlows rules are, both, not Condorcet-consistent.



A classification of ranking rules

Definition (*M*-ordinality)

A ranking rule is ***M*-ordinal** if its ranking result only depends on the order of the majority margins.

Property (*M*-ordinal rules)

*Slater's, Copeland's, Kohler's and the RankedPairs rule are all *M*-ordinal. The Kemeny and the NetFlows rules are not *M*-ordinal.*

Definition (*M*-invariance)

A ranking rule is ***M*-invariant** if its ranking result only depends on the sign of the majority margins.

Property (*M*-invariant rules)

*Slater's and Copeland's rule are both *M*-invariant. Kohler's and the RankedPairs rules are not *M*-invariant.*



A classification of ranking rules

Definition (*M*-ordinality)

A ranking rule is ***M*-ordinal** if its ranking result only depends on the order of the majority margins.

Property (*M*-ordinal rules)

Slater's, Copeland's, Kohler's and the RankedPairs rule are all *M*-ordinal.
The Kemeny and the NetFlows rules are not *M*-ordinal.

Definition (*M*-invariance)

A ranking rule is ***M*-invariant** if its ranking result only depends on the sign of the majority margins.

Property (*M*-invariant rules)

Slater's and Copeland's rule are both *M*-invariant. Kohler's and the RankedPairs rules are not *M*-invariant.



A classification of ranking rules

Definition (*M*-ordinality)

A ranking rule is ***M*-ordinal** if its ranking result only depends on the order of the majority margins.

Property (*M*-ordinal rules)

Slater's, Copeland's, Kohler's and the RankedPairs rule are all *M*-ordinal.
The Kemeny and the NetFlows rules are not *M*-ordinal.

Definition (*M*-invariance)

A ranking rule is ***M*-invariant** if its ranking result only depends on the sign of the majority margins.

Property (*M*-invariant rules)

Slater's and Copeland's rule are both *M*-invariant. Kohler's and the RankedPairs rules are not *M*-invariant.



A classification of ranking rules

Definition (*M*-ordinality)

A ranking rule is ***M*-ordinal** if its ranking result only depends on the order of the majority margins.

Property (*M*-ordinal rules)

Slater's, Copeland's, Kohler's and the RankedPairs rule are all *M*-ordinal.
The Kemeny and the NetFlows rules are not *M*-ordinal.

Definition (*M*-invariance)

A ranking rule is ***M*-invariant** if its ranking result only depends on the sign of the majority margins.

Property (*M*-invariant rules)

Slater's and Copeland's rule are both *M*-invariant. Kohler's and the RankedPairs rules are not *M*-invariant.

A classification of ranking rules by Cl. Lamboray




FIGURE – 4. *SWR* : single weak ranking, *MLR* : multiple linear rankings



Which ranking rule should we use

- There is no perfect ranking rule (cf Arrow's theorem).
- What properties of a ranking rule are useful or required?
- Axiomatic characterizations of the ranking rules.
- More or less consensual global rankings?
- Correlation with the majority margins $M(x, y)$?
- Fitness for big data : computational complexity?



Which ranking rule should we use

- There is no perfect ranking rule (cf Arrow's theorem).
- What properties of a ranking rule are useful or required ?
- Axiomatic characterizations of the ranking rules.
- More or less consensual global rankings ?
- Correlation with the majority margins $M(x, y)$?
- Fitness for big data : computational complexity ?



Which ranking rule should we use

- There is no perfect ranking rule (cf Arrow's theorem).
- What properties of a ranking rule are useful or required?
- Axiomatic characterizations of the ranking rules.
- More or less consensual global rankings?
- Correlation with the majority margins $M(x, y)$?
- Fitness for big data : computational complexity?



Which ranking rule should we use

- There is no perfect ranking rule (cf Arrow's theorem).
- What properties of a ranking rule are useful or required?
- Axiomatic characterizations of the ranking rules.
- More or less consensual global rankings?
- Correlation with the majority margins $M(x, y)$?
- Fitness for big data : computational complexity?



Which ranking rule should we use

- There is no perfect ranking rule (cf Arrow's theorem).
- What properties of a ranking rule are useful or required ?
- Axiomatic characterizations of the ranking rules.
- More or less consensual global rankings ?
- Correlation with the majority margins $M(x, y)$?
- Fitness for big data : computational complexity ?



Which ranking rule should we use

- There is no perfect ranking rule (cf Arrow's theorem).
- What properties of a ranking rule are useful or required?
- Axiomatic characterizations of the ranking rules.
- More or less consensual global rankings?
- Correlation with the majority margins $M(x, y)$?
- Fitness for big data : computational complexity?

Example (Which is the *better* social ranking?)

```
>>> from votingProfiles import *
>>> v = LinearVotingProfile('example1')
>>> v.showHTMLVotingHeatmap(rankingRule='Copeland')
>>> v.showHTMLVotingHeatmap(rankingRule='NetFlows')
```

criteria	v5	v3	v2	v4	v1
weights	2	4	7	4	8
tau(*)	0.60	0.40	0.40	0.20	0.20
c	5	4	3	2	4
b	3	3	4	5	3
e	2	2	5	3	2
d	4	5	2	4	1
a	1	1	1	1	5

criteria	v2	v5	v4	v3	v1
weights	7	2	4	4	8
tau(*)	0.60	0.40	0.40	0.20	0.00
b	4	3	5	3	3
c	3	5	2	4	4
e	5	2	3	2	2
d	2	4	4	5	1
a	1	1	1	1	5

Figure – 5. Copeland – versus NetFlows ranking.

(*) tau : Ordinal (Kendall) correlation between *marginal* and *global* ranking.
The ranks are of *reversed Borda type* : $w_1 = 5, w_2 = 4, w_3 = 3, w_4 = 2, w_5 = 1$.

Example (Correlations with the majority margins)

```
>>> cd.recodeValuation(1,1) # normalizing the majority margins
>>> from linearOrders import CopelandOrder, NetFlowsOrder
>>> cop = CopelandOrder(cd); cop.copelandOrder
['a', 'd', 'e', 'b', 'c']
>>> corr = cd.computeOrderCorrelation(cop.copelandOrder)
>>> cd.showCorrelation(corr)
Correlation indexes:
Crisp ordinal correlation : +1.000
Valued equivalence       : +0.320
Epistemic determination  : 0.320
>>> nf = NetFlowsOrder(cd); nf.netFlowsOrder
['a', 'd', 'e', 'c', 'b']
>>> corr cd.computeOrderCorrelation(nf.netFlowsOrder)
Correlation indexes:
Crisp ordinal correlation : +0.925
Valued equivalence       : +0.296
Epistemic determination  : 0.320
```

In this example, the *Condorcet-consistency* property assures that the *Copeland*, *Kemeny* and *Slater* ranking rules all deliver a perfectly matching ordinal result ($\tau = +1.0$), whereas the *Net-Flows* rule inverts the top candidates ($\tau = +0.925$). The epistemic determination of the majority margins is 0.32, ie the ordinal correlations are supported here in average by a $(1.0 + 0.32)/2 = 66\%$ majority, ie 16/25 voters.



Exercise (Claude Lamboray, PhD thesis p. 35)

Apply all the previous ranking rules on the following profile of 10 weighted linear orders defined on 4 candidates $\{a, b, c, d\}$ as shown below ; discuss the results.

4 : abcd	3 : bcad
4 : dcab	4 : dabc
4 : cabd	2 : cdab
5 : dbca	2 : bacd
1 : cbda	1 : acdb



Exercise (*votingProfiles* module extension)

*Suppose that some voters will not provide a complete linear ranking of all the candidates. Develop Python code based on the *votingProfiles* module, that implements all the previously defined ranking rules and renders a corresponding ranking when given a *LinearVotingProfile* instance with partial ballots.*



Digraph3 software resources

- Documentation index :
<https://digraph3.readthedocs.io/en/latest/index.html>
- Tutorials :
<https://digraph3.readthedocs.io/en/latest/tutorial.html>
- Reference manual :
<https://digraph3.readthedocs.io/en/latest/techDoc.html>
- Advanced topics :
<https://digraph3.readthedocs.io/en/latest/pearls.html>